

USES:

Program listings, screen copy, charts, reports, mailing list, graphics, etc.

FEATURES:

Two color printing capability. Uses standard 2.75" wide plain paper roll, 40-column width capability, upper/lower case characters, graphic character set, dot addressable graphics, reverse character mode, user selection of two character sets, wraparound facility permits printing of text lines longer than 40 characters, built-in self-test mode.

SPECIFICATIONS:

Print Method—Impact dot matrix with 7-wire printhead. Print Rate—Approximately 65 characters per second. Print Format—240 dots per line.

Character Size - (5 x 7 matrix) 0.049" W x 0.094" H.

Paper – 2.75" W normal paper roll. Ribbon – Two-color ribbon spool. Colors – Black and red.

Manual Controls - Power On/Off, Paper Feed, Select.

Indicators—Power On LED, Select LED. Reliability—MCBF equal to 1,500,000 lines. Power—2 watts (idle), 7 watts (printing). Dimensions—10" W x 8" L x 3.6" H. Transformer Included. 90-Day Warranty.

OPTIONAL INTERFACES:

PARALLEL - 8-bit ASCII, plus STROBE, BUSY, and ACK. SERIAL—Selectable BAUD rates (300, 1200, 2400).

FIDELITY ELECTRONICS, LTD.
8800 N.W. 36th STREET, MIAMI, FLORIDA 33178, 305-888-1000/594-1000

© Copyright 1983 by Fidelity Electronics, Ltd.

*Desk Companion is a trademark of Fidelity Electronics Ltd.

*VIC-20° and Commodore-84° are trademarks of Commodore
Business Machines, Inc.
All product data subject to change without notice.

All Fidelity Products are Quality Made in U.S.A.

Fidelity Impact 40 printer

(photo copyright © by http://www.schaakcomputers.nl/) (600 dpi